

Patch Cord LC UPC to LC UPC 3.00mm Simplex MM OM3

Patchcord LC to LC UPC Simplex MPO3 35m

Patch Cord LC UPC to LC UPC 3.00mm Simplex MM OM3

Variants

15M 3.00mm 10M 3.00mm 5M 3.00mm 1M 3.00mm 3M 3.00mm 2M 3.00mm
20M 3.00mm

Details

LC–LC Multimode Fiber Patch Cord (OM3 50/125µm)

Specification	Details
Connector Type	LC / LC
Polish Type	UPC
LC Boot Type	Standard Boot, 12/18mm Short Boot
SC Boot Type	Standard Boot, 25mm Short Boot
Fiber Mode	OM3 50/125µm
Wavelength	850 / 1300 nm
Fiber Grade	Bend Insensitive
Flame Rating	Riser (OFNR) / LSZH
Min. Bend Radius (Fiber)	7.5 mm
Min. Bend Radius (Cable)	20D / 10D (Dynamic / Static)
Fiber Count	Simplex / Duplex
Cable Diameter (OD)	1.6 / 2.0 / 3.0 mm
Insertion Loss	? 0.3 dB

Specification	Details
Return Loss	? 30 dB
Attenuation @ 850 nm	3.5 dB/km
Attenuation @ 1300 nm	1.5 dB/km

© 2026 | Phone: +977 9851248419 | Email: info@dtechtrading.com | Website: <https://demoshop.com>. All rights reserved.