

# Patch Cord LC UPC to LC UPC 3.00mm Simplex MM OM3

Patchcord LC to LC UPC Simplex MPO3 35m

Patch Cord LC UPC to LC UPC 3.00mm Simplex MM OM3

## Variants

15M 3.00mm 10M 3.00mm 5M 3.00mm 1M 3.00mm 3M 3.00mm 2M 3.00mm  
20M 3.00mm

## Details

### LC–LC Multimode Fiber Patch Cord (OM3 50/125µm)

Specification	Details
Connector Type	LC / LC
Polish Type	UPC
LC Boot Type	Standard Boot, 12/18mm Short Boot
SC Boot Type	Standard Boot, 25mm Short Boot
Fiber Mode	OM3 50/125µm
Wavelength	850 / 1300 nm
Fiber Grade	Bend Insensitive
Flame Rating	Riser (OFNR) / LSZH
Min. Bend Radius (Fiber)	7.5 mm
Min. Bend Radius (Cable)	20D / 10D (Dynamic / Static)
Fiber Count	Simplex / Duplex
Cable Diameter (OD)	1.6 / 2.0 / 3.0 mm
Insertion Loss	? 0.3 dB

Specification	Details
Return Loss	? 30 dB
Attenuation @ 850 nm	3.5 dB/km
Attenuation @ 1300 nm	1.5 dB/km

---

© 2026 | Phone: +977 9851248419 | Email: [info@dtechtrading.com](mailto:info@dtechtrading.com) | Website: <https://demoshop.com>. All rights reserved.