

# Cassette SC/UPC

Cassette SC/UPC

## Variants

1\*4 1\*8 1\*2

## Details

# PLC Splitter Cassette Type SC UPC

## Technical Specifications

| Category                 | Specification                         |
|--------------------------|---------------------------------------|
| Product Type             | PLC Splitter (Cassette Type)          |
| Configuration            | 1 x N                                 |
| Fiber Type               | Single Mode G.657A1 / G.652D          |
| Operating Wavelength     | 1260 ~ 1650 nm                        |
| Insertion Loss (P Grade) | ? 10.4 dB                             |
| Insertion Loss (S Grade) | ? 10.6 dB                             |
| PDL                      | ? 0.3 dB                              |
| Loss Uniformity          | ? 1.0 dB                              |
| Return Loss              | ? 55 dB (P Grade) / ? 50 dB (S Grade) |
| Directivity              | ? 55 dB                               |
| Connector Type           | SC/UPC (Optional SC/APC)              |
| Cable Length             | 1.0 m (Customizable)                  |

|                       |                        |
|-----------------------|------------------------|
| Fiber Diameter        | 0.9 mm / 2.0 mm        |
| Housing Type          | ABS Cassette / LGX Box |
| Operating Temperature | -40°C to +85°C         |
| Storage Temperature   | -40°C to +85°C         |
| Dimension (L x W x H) | ~120 x 80 x 18 mm      |

---

© 2026 | Phone: +977 9851248419 | Email: [info@dtechtrading.com](mailto:info@dtechtrading.com) | Website: <https://demoshop.com>. All rights reserved.