

# Cassette SC/UPC

Cassette SC/UPC

## Variants

1\*4 1\*8 1\*2

## Details

# PLC Splitter Cassette Type SC UPC

## Technical Specifications

Category	Specification
Product Type	PLC Splitter (Cassette Type)
Configuration	1 x N
Fiber Type	Single Mode G.657A1 / G.652D
Operating Wavelength	1260 ~ 1650 nm
Insertion Loss (P Grade)	? 10.4 dB
Insertion Loss (S Grade)	? 10.6 dB
PDL	? 0.3 dB
Loss Uniformity	? 1.0 dB
Return Loss	? 55 dB (P Grade) / ? 50 dB (S Grade)
Directivity	? 55 dB
Connector Type	SC/UPC (Optional SC/APC)
Cable Length	1.0 m (Customizable)

Fiber Diameter	0.9 mm / 2.0 mm
Housing Type	ABS Cassette / LGX Box
Operating Temperature	-40°C to +85°C
Storage Temperature	-40°C to +85°C
Dimension (L x W x H)	~120 x 80 x 18 mm

---

© 2026 | Phone: +977 9851248419 | Email: [info@dtechtrading.com](mailto:info@dtechtrading.com) | Website: <https://demoshop.com>. All rights reserved.