

# 4 Channel DWDM Fiber Mux Demux in Cassete Type

## Variants

RX: C53-C56/ TX:C25-C28, LC/UPC    RX: C25-C28/ TX:C53-C56, LC/UPC

## Details

# 4 Channel DWDM MUX / DEMUX (Reverse Channel Mapping)

4 Channel DWDM MUX/DEMUX designed to combine and separate multiple wavelengths over a single fiber. This variant uses reverse channel mapping, ideal for bidirectional transmission in ISP, metro, and data center networks.

## Key Specifications

Parameter	Specification
Device Type	Passive DWDM MUX / DEMUX
Channel Count	4 Channel
Form Factor	Cassete Type (Rack Mount Compatible)
Channel Spacing	100 GHz (ITU-T Grid)
Connector Type	LC / UPC
Fiber Type	Single Mode (SMF - G.652D / OS2)
Insertion Loss	? 2.5 dB (Typical)
Isolation	? 30 dB
Return Loss	? 45 dB
Directivity	? 50 dB

Operating Temperature	-5°C to +70°C
Storage Temperature	-40°C to +85°C
Packaging	ABS Cassette Module

---

© 2026 | Phone: +977 9851248419 | Email: [info@dtechtrading.com](mailto:info@dtechtrading.com) | Website: <https://demoshop.com>. All rights reserved.