

Fiber Optic Adapter

Fiber Optic Adapter

Variants

FC UPC to FC UPC 0db LC UPC to LC UPC 5db SC UPC to SC UPC 5db LC to LC Dx OM4 SC to SC APC 0db LC to LC UPC Duplex 0db SC UPC to LC UPC 0db SC UPC to SC UPC 0db LC to LC APC Dx 0db

Details

Category	Specification
Product Type	Fiber Optic Hybrid Adapter
Adapter Type	SC/SC, LC/LC, FC/FC (Available Variants)
Connector 1	SC UPC
Connector 2	LC UP
Polish Type	UPC (Ultra Physical Contact)
Fiber Compatibility	Single Mode / Multimode

Housing Material	PBT + Glass Fiber (GF)
Sleeve Material	
Adapter Color	SC: Beige / LC: Blue or Aqua
Mounting Type	Flange / Slim Type
Clip Type	Stainless Steel Clip
Insertion Loss	Low (Typical ? 0.2 dB)
Return Loss	High (Typical ? 50 dB)
Installation Temperature	-20°
Operating Temperature	-40°
Storage Temperature	-55°C to
Compliance Standards	GR-326, IEC 61754, ISO/IEC 24764, IEC 61034, EN 5

Packaging	Individual / Bulk Packaging
Configuration	Simplex / Duplex Options