

# ADSS Tension Clamp

---

ADSS Tension Clamp

## Variants

6-9mm 2-4mm 12-17mm 8-12mm

## Details

# ADSS Anchoring Clamp – Specifications

SN	Suitable Cable Diameter (mm)	Material (Body / Wedges / Thimble)
1	3 – 7 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)
2	4 – 8 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)
3	6 – 10 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)
4	6 – 10 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)
5	8 – 12 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)
6	10 – 14 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)
7	8 – 12 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)

<b>SN</b>	<b>Suitable Cable Diameter (mm)</b>	<b>Material (Body / Wedges / Thimble)</b>
8	10 – 14 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)
9	12 – 16 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)
10	14 – 18 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)
11	16 – 20 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)