ADSS Tension Clamp

ADSS Tension Clamp

Variants

Clamp 12-17mm Clamp 6-9mm Clamp 2-4mm Clamp 8-12mm

Details

The **ADSS Anchoring Clamp** is designed for dead-end fixing and tension support of ADSS optical fiber cables. It provides strong cable grip, stable holding performance, and safe installation for aerial fiber optic networks.

Technical Specifications

SN	Cable Diameter	Body / Wedges / Thimble	Bail Material	
1	3 – 7 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)	Stainless Steel	
2	4 – 8 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)	Stainless Steel	
3	6 – 10 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)	Stainless Steel	
4	6 – 10 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)	Stainless Steel	

SN	Cable Diameter	Body / Wedges / Thimble	Bail Material	
5	8 – 12 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)	Stainless Steel	
6	10 – 14 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)	Stainless Steel	
7	8 – 12 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)	Stainless Steel	
8	10 – 14 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)	Stainless Steel	
9	12 – 16 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)	Stainless Steel	
10	14 – 18 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)	Stainless Steel	
11	16 – 20 mm	UV Protected Thermoplastic (Nylon PA66 + Fiberglass)	Stainless Steel	

Note: Please choose the correct clamp size according to the ADSS cable outer diameter and required breaking load.

© 2026 | Phone: +977 9851248419 | Email: info@dtechtrading.com | Website: https://demoshop.com. All rights reserved.