

Reyee Wi-Fi 6 AX1800 Ceiling-Mount Access Point

Variants

RG-RAP62

Details

Wi-Fi 6 Dual Band Access Point

This Wi-Fi 6 access point is designed for high-performance wireless connectivity in enterprise, office, and indoor environments. It features dual-radio design with MU-MIMO technology, ensuring efficient data transmission, improved coverage, and stable connectivity for multiple users.

Wi-Fi Radio Specifications

Parameter	Specification
Radio Design	Dual-Radio
Spatial Streams	4 Streams (2x2 per band)
2.4 GHz	2x2 MU-MIMO (573 Mbps)
5 GHz	2x2 MU-MIMO (1201 Mbps)
Maximum Data Rate	1774 Mbps
6 GHz Support	Not Supported

Antenna Specifications

Band	Antenna Type
2.4 GHz	2 Built-in Omnidirectional Antennas

5 GHz	3 Built-in Omnidirectional Antennas
-------	-------------------------------------

Port Specification

Parameter	Specification
Ethernet Port	1 × 10/100/1000BASE-T

Power Specification

Parameter	Specification
Power Supply	DC Adapter / PoE / PoE+
Local Power	12V, 1.5A DC
DC Connector Size	5.5 mm (OD) / 2.1 mm (ID)
Power Consumption	? 12.95 W
PoE Budget	Not Applicable

Physical Specifications

Parameter	Specification
Dimensions	Ø175 × 39 mm
Color	White
Weight	? 0.4 kg

Environment & Reliability

Parameter	Specification
Operating Temperature	0°C to 40°C

Mounting	Ceiling / Wall
IP Rating	IP41

© 2026 | Phone: +977 9851248419 | Email: info@dtechtrading.com | Website: <https://demoshop.com>. All rights reserved.