

P524 (2*200G Muxponder)

P524 (2*200G Muxponder)

Details

2x200G Muxponder Service Card – P524

The P524 Muxponder service card from D-TECH Trading supports mapping 4 × 100G optical signals from the client side into 2 × OTUC2 signals. It also enables interconversion between OTUC2 signals and WDM optical wavelengths compliant with ITU-T standards. The line side adopts pluggable CFP2-DCO modules for ultra-long-distance transmission using advanced coherent detection technology.

Applications

Use Cases
Suitable for metropolitan and long-distance transmission networks up to 1000 km
Suitable for high-capacity DCI transmission in enterprises, campuses, and cloud computing environments
Suitable for 200G links in existing OTN / DWDM infrastructures

Technical Specifications

Feature	Description
Function	Supports 4 × 100G service signals mapping to 2 × OTUC2 signals

Slot / Line Side	<p>2 × CFP2 ports (200G / 400G CFP2-DCO, pluggable)</p> <p>Supports adjustable wavelength: 191.35 ~ 196.1 THz</p> <p>Supports adjustable transmit power</p> <p>Supports 100G / 200G rate switching</p> <p>Supports single-fiber bidirectional transmission (optional)</p>
Client Side	Supports 4 × QSFP28 modules (hot-pluggable)
Frame Format & Overhead	Based on ITU-T G.709 recommendations
OTN Function	<p>ODUk (k = 4, C2): supports PM and related functions</p> <p>OTUk (k = 4, C2): supports SM functions</p>
Supported Services	100GE, 100GE FlexE, OTU4
Time Delay Measurement	Online delay measurement based on ODU layer
Loopback	Supports line-side and client-side loopback
LLDP	Ethernet supported
Protection Function	<p>No client-side sensing during protection reversal (with optical protection board, optional)</p> <p>Supports OTN performance monitoring and alarm monitoring</p>
Performance Monitoring & Alarm	<p>Supports optical module temperature, current, and optical power monitoring</p> <p>Supports Ethernet RMON monitoring</p> <p>Supports Telemetry</p>