

FTTH PON & CATV WDM OPTICAL RECEIVER

FTTH PON & CATV WDM OPTICAL RECEIVER

Variants

FWR-8610RW

Details

FTTH PON & CATV WDM Optical Receiver

Category	
Model	FWR-8610RW
Product Type	FTTH PON + CATV WDM Optical R
Application	FTTH, CATV, Triple-play Networks
Technology	High Isolation WDM + RF AGC
Fiber Interface	SC/UPC or SC/APC
Optical Wavelength (Input)	1310 / 1490 / 1550 nm
Optical Wavelength (Output)	1310 / 1490 nm

Category	
CATV Operating Wavelength	1540 – 1560 nm
Channel Separation	? 40 dB
Responsivity	? 0.9 A/W
Optical Receive Power	+3 to -18 dBm
Optical Indicator	LED (? -15 dBm)
Return Loss	? 55 dB

RF Performance

Category	
Frequency Range	47 – 1000 MHz
Flatness	? ± 1 dB
Output Level	82 / 76 / 70 dB μ V (± 1 dB)
Output Adjustment	0 ~ -18 dB
RF Output Interface	Metric (Single Output)

Category	
RF Return Loss	? 14 dB (75?)
CNR / MER	? 44 / 34 dB
CTB / CSO / HUM	? 65 / ? 60 / ? 60 dB

Power & Environment

Category	
Power Supply	AC 155–255V ? DC 12V
Power Consumption	? 5 W
Operating Temperature	-35°C to +50°C
Storage Temperature	-40°C to +75°C
Humidity	5% – 90%
Dimensions	130 × 60 × 22 mm

Packing Details

Category	
Packing	1 pc / box
Carton Quantity	80 pcs / carton

© 2026 | Phone: +977 9851248419 | Email: info@dtechtrading.com | Website: <https://demoshop.com>. All rights reserved.