

Thermal Stripper

COMWAY Fiber Stripper

Thermal Stripper

Variants

CS-06

Details

Fiber Stripping Tool CS-06 – Specifications

Product Specifications

Parameter	Details
Model	CS-06
Applicable Fiber	Bundle fiber / Bare fiber / Pigtail / Ribbon fiber / Invisible fiber
Number of Stripped Fiber	Bundle fiber: 1–12 cores Bare fiber: 1–36 cores Pigtail fiber: 1 core Ribbon fiber: 2–36 cores Invisible fiber: 1–12 cores
Cladding Diameter	125 μm
Coating Diameter	200 – 400 μm
Stripping Length	Up to 30 mm
Power Mode	Normal Mode / Power Save Mode
Temperature Setting	Approx. 90°C / 100°C / 110°C / 140°C

Heating Time	Normal Mode: Approx. 4s Power Save Mode: Approx. 5s
Battery Capacity	Lithium-ion battery 7.4V / 2000mAh
Endurance	Approx. 660 stripping cycles per full charge
Power Supply	USB Type-C (5V–20V, Max 20W)
Operating Condition	Temperature: -10°C to +40°C Humidity: 0% – 95%
Dimensions	108 (L) × 48 (W) × 32 (H) mm
Weight	290 g

[Download Comway-Thermal Stripper : Data sheet in PDF File](#)