

Fiber Optic Patch Cord Simplex LC UPC to SC APC

Fiber Optic Patch Cord Simplex LC UPC to SC APC

Variants

5M 3.00mm 1M 3.00mm 2M 3.00mm 3M 3.00mm

Details

Fiber Optic Patch Cord – Simplex LC UPC to SC APC (Single-Mode)

Key Features

No.	Features
1	High-precision LC-UPC to SC-APC connectors
2	Low insertion loss and excellent return loss
3	Suitable for FTTH, FTTx, OLT, ONU, Router, Media Converter
4	Single-mode G.652D compliant fiber
5	2.0mm or 3.0mm LSZH / PVC jacket
6	Available in multiple lengths (1m–30m, custom)

Technical Specifications

Parameter	Specification
Connector Type	LC UPC to SC APC

Fiber Type	Single-Mode (SM) G.652D
Mode	Simplex
Jacket Material	LSZH or PVC
Cable Diameter	2.0 mm / 3.0 mm
Insertion Loss	? 0.30 dB (typical)
Return Loss (UPC)	? 50 dB
Return Loss (APC)	? 60 dB
Operating Wavelength	1310 nm / 1550 nm
Length Options	1m to 30m (custom available)
Color	Yellow (Single-Mode standard)
Temperature Range	?40°C to +85°C