

Drop Cable SC APC to SC APC

Drop Cable SC APC to SC APC

Variants

100M 50M 75M 30M 200M 125M 150M

Details

FTTH Drop Cable SC APC to SC APC

Cable Structure

Parameter	Details
Fiber Type	G.657A1 (Bend-Insensitive)
Number of Fibers	1 Core
Strength Member	2 x 0.45 mm Steel Wires
Messenger Wire	1.0 mm Galvanized Steel (7 x 0.33 mm strands)
Cable Dimension	2.0 x 5.0 mm
Cable Weight	1 kg/km ($\pm 5\%$)
Cable Print	D-TECH / Production Date

Cable Performance

Parameter	Value
-----------	-------

Long-Term Tensile Load	300 N
Short-Term Tensile Load	600 N
Long-Term Crush Load	1000 N
Short-Term Crush Load	2200 N
Minimum Bend Radius (Static)	20 mm
Minimum Bend Radius (Dynamic)	40 mm
Installation Temperature	-10°C to +40°C
Operating Temperature	-40°C to +60°C

Connector Specification

Parameter	UPC	APC
Fiber Mode	Single Mode (G.657A1)	
Cord Type	Simplex	
Length Options	30m, 50m, 75m, 100m, 150m, 200m, 300m	
Insertion Loss	? 0.3 dB	? 0.3 dB
Return Loss	? 50 dB	? 55 dB