ADSS J Hook

Overhead Line Electric Accessories Steel Pole Install Fiber Cable Suspension Clamp

---

ADSS J Hook

Variants

J hook 15~20mm J hook 04~08mm J hook 10~15mm J hook 08~12mm

Details

Specification of Suspension Clamps

The suspension clamp is used for the direct suspension of round fiber optic ADSS cables with Ø04 to 20mm on short spans (max 100m) at intermediate poles on straight routes.

SN	Cable Dia. (mm)	Materials	Breaking Load	Weight
1	04 ~ 08 mm	Electroplated Steel + Neoprene + Protected Steel	4000N	0.175 kg
2	08 ~ 12 mm	Hot Dip Galvanized Steel	5000N	0.555 kg
3	10 ~ 15 mm	—	—	—
4	15 ~ 20 mm	—	—	—

Installation Method

Suspended from Hook Bolt	Installed on 14mm or 16mm hook bolt on drilled wood poles
Pole Banding	Installed on wood, round concrete, or metallic poles using 20mm pole bands and buckles
Bolt Fixing	Secured with 14mm or 16mm bolt on drilled wood poles

---

© 2026 | Phone: +977 9851248419 | Email: info@dtechtrading.com | Website: https://demoshop.com. All rights reserved.