

# Drop Cable SC UPC to SC APC

---

Drop Cable SC UPC to SC APC

## Variants

150M 75M 100M 200M 50M 30M 300M 125M

## Details

### Cable Structure of Drop Cable:

Parameter	Details
Type of Fiber	G.657A1
No. of Fibers	1
Strength Member	2pcs*0.45mm steel wires
Messenger Wire	1. 0mm galvanized stranding steel wire (7pcs*0.33mm steel wire)
Cable Dimension	2.0*5.0mm
Cable Weight	1kg/km ( $\pm 5\%$ )
Cable Print	Company name: D-Tech Trading Production time **

### Cable Performance of Drop Cable:

Long Term Tension Load	300N
Short Term Tension Load	600N
Long Term Crush Load	1000N
Short Term Crush Load	2200N
Minimum Static Bending Radius	20mm

Minimum Dynamic Bending Radius	40mm
Installing Temperature	-10°C to +40°C
Operating Temperature	-40°C to +60°C

## Connector of Drop Cable:

Mode	Single-mode: G657A1	
Cord type	Simplex	
length(M)	30m,50m,75m,100m,150m,200m, 300m etc	
Polish	UPC	APC
Insertion Loss	?0.3dB	?0.3dB
Return Loss	?50dB	?55dB