

ADSS Suspension Clamp Span 100M

ADSS Suspension Clamp Span 100M

Variants

14-16mm 12-14mm 16-18mm 9-12mm

Details

Suspensions set for 100m span

Description:

The ADSS suspension clamp is used to connect the ADSS cables on the straight pole/towers. They feature in sample structures, easy installation and lower cost.

1. Configuration:

S.NO	Description	Code	Material	Qty	Weight(kg)
1	U clevis	U-5	Forged steel	1	0.3
2	Housing		Aluminum alloy,length:100mm	1	0.4

3		Synthetic rubber length:120m m	1	0.15
Total weight(kg)				0.85

Type 1:

- 1- Anchor shackle: forged steel
- 2- Housing: aluminum alloy
- 3- Rubber insert: synthetic rubber
- 4- Bolt, nut, cotter pin

Type 2:

- 1- Stainless steel band (1.2m)
- 2- Stainless steel base: 1pcs
- 3- Rubber insert : synthetic rubber
- 4- Housing: aluminum alloy
- 5- Bolt, nut, washer, spring washer: 1set

2. Features:

Simple structures, easy installation, and lower cost.

Applications: Poles/towers with span of less than 100m, and line angle of less than 15°

4. Technical Data:

RTS: greater than 20kN recommended span length: 100m

SN	Cable Diameter (mm)	Armor Rods (mm)	Anchor Shackle
1	9.0-12	0	U-5
2	12-14	0	U-5
3	14-16	0	U-5
4	16-18	0	U-5