

ADSS Suspension Clamp Span 100M

ADSS Suspension Clamp Span 100M

Variants

9-12mm 16-18mm 14-16mm 12-14mm

Details

Suspension Set for 100m Span

Description

The ADSS suspension clamp is used to connect ADSS cables on straight poles or towers. It features a simple structure, easy installation, and lower cost.

1. Configuration

S.NO	Description	Code	Material	Qty	Weight (kg)
1	U Clevis	U-5	Forged Steel	1	0.3
2	Housing	—	Aluminum Alloy, Length: 100mm	1	0.4
3	Synthetic Rubber	—	Length: 120mm	1	0.15
Total Weight (kg)					0.85

Type 1

1	Anchor Shackle: Forged Steel
2	Housing: Aluminum Alloy
3	Rubber Insert: Synthetic Rubber

4	Bolt, Nut, Cotter Pin
---	-----------------------

Type 2

1	Stainless Steel Band (1.2m)
2	Stainless Steel Base: 1 pc
3	Rubber Insert: Synthetic Rubber
4	Housing: Aluminum Alloy
5	Bolt, Nut, Washer, Spring Washer: 1 Set

2. Features

Simple structure, easy installation, and lower cost

Applications

Recommended Use	Poles or towers with span less than 100m and line angle less than 15°
-----------------	---

4. Technical Data

RTS	Greater than 20 kN
Recommended Span Length	100m

SN	Cable Diameter (mm)	Armor Rods (mm)	Anchor Shackle
1	9.0 – 12	0	U-5
2	12 – 14	0	U-5
3	14 – 16	0	U-5
4	16 – 18	0	U-5

