

Fiber Optic Enclosure Vertical

Fiber Optic Enclosure Vertical

Variants

96 Cores 72 Cores 12 Cores 24 Cores 48 Cores

Details

Fiber Optic Splice Closure

GJS-901-2

Overview

GJS-901-2 fiber optic splice closures (FOSC) are used to distribute, splice, and store the outdoor optical cables which enter and exit from the ends of the closure. There are two connection ways: direct connection and splitting connection. Applicable to situations such as overhead, man-well or pipeline, embedded situation etc.

Features

- 1 The protection grade reaches IP 68.
- 1 Aerial and wall-mounting.
- 1 Ambient temperature ranges from -40 to 65?.

- 1 The closure is of small volume, big capacity and convenient maintenance.
- 1 The closure casing is made of quality engineering plastics, and of good performance of anti-erosion against acid and alkali salt, anti-aging, as well as smooth appearance and reliable mechanical structure.
- 1 The mechanical structure is reliable and has the performance of resisting wild environment and intensive climate changes and serious working environment.
- 1 The splice trays (FOST) inside the closure are turn-able like booklets, and have adequate curvature radius and space for winding optical fiber to make sure the curvature radius for optical winding 40 mm. Each optical cable and fiber can be operated individually.

Dimensions and Capacity			
Outside Dimensions (Height*Diameter)			299mm*178mm
Weight (excluding outside box)			1550g - 1740g
Number of Inlet / Outlet Ports			4 pieces in general
Diameter of Fiber Cable			3-?8mm ~ ?20mm 1-20*35mm
Capacity of FOSC			Bunchy: 6 cores - 24 cores
Main Components			
Name of Components	Quantity	Usage	Remarks
FOSC Cover	1 piece	Protecting fiber cable splices in whole	Height*Diameter: 226*132 (mm)

Splice Tray (FOST)	Max. 4 trays (bunchy)	Fixing heat shrink protective sleeve and holding fibers	Bunchy:12 (cores)
Fiber Holding Tray	1 piece	Holding fibers with protective coat	N/A
Base	1 set	Fixing internal and external structure	N/A
Plastic Hoop	1 set	Fixing between FOSC cover and base	N/A
Seal Fitting	1 piece	Sealing between FOSC cover and base	N/A
Pressure Testing Valve	1 set	After inject air, it is used for pressure testing and sealing testing	Configuration as per requirement.
Earthing Deriving Device	1 set	Deriving metallic parts of fiber cables in FOSC for earthing connection	Configuration as per requirement.

Main Accessories and Special Tools

Name of Components	Quantity	Usage	Remarks
Heat Shrink Protective Sleeve	N/A	Protecting fiber splices	Configuration as per capacity
Nylon Tie	N/A	Fixing fiber with protective coat	Configuration as per capacity
Heat Shrink Fixing Sleeve (single)	N/A	Fixing and sealing single fiber cable	Configuration as per requirement
Heat Shrink Fixing Sleeve (mass)	N/A	Fixing and sealing mass of fiber cable	Configuration as per requirement
Branching Clip	N/A	Branching fiber cables	Configuration as per requirement
Earthing Wire	1 piece	Putting through between earthing devices	N/A

Desiccant	1 bag	Put into FOSC before sealing for desiccating air	N/A
Labeling Paper	1 piece	Labeling fiber	N/A
Special Wrench	1 piece	Tightening nut of reinforced core	N/A
Metal Hoop	1 set	For wall mounting and pole hugging	N/A
Buffer Tube	Customize	Hitched to fibers and fixed with FOST, managing buffer	Configuration as per requirement
Shipping Information			
Specification	Carton Size	Capacity	Net Weight
Inner Box	170mm*155mm*301 pc	1.65kg-1.85kg	Configuration as per weight
Outer Box	490mm*370mm*6212 pcs	19.8kg - 22.2kg	Configuration as per weight

Part Details



© 2026 | Phone: +977 9851248419 | Email: info@dtechtrading.com | Website: <https://demoshop.com>. All rights reserved.