

WIFI-6 AC1200 Full Router JIR-AC666R2

WIFI-6 AC1200 Full Router JIR-AC666R2

Details

Product Overview of WIFI-6 AC1200 Full Router JIR-AC666R2:

Experience cutting-edge Wi-Fi 6 technology with our AC1200 Full Router, JIR-AC666R2, offering faster speeds, expanded capacity, and minimized network congestion.

With next-generation speeds of up to 1.5 Gbps, our dual-band router delivers lightning-fast performance (1201 Mbps on the 5 GHz band and 300 Mbps on the 2.4 GHz band).

Empower your network to handle more devices effortlessly, thanks to Wi-Fi 6 technology's innovative OFDMA and MU-MIMO features, reducing latency and enhancing connectivity.

Powered by a robust 1.5 GHz tri-core processor, our router ensures seamless communication between your devices, eliminating buffering and ensuring smooth operation.

Enjoy unparalleled Wi-Fi coverage with the AC1200 Full Router JIR-AC666R2, utilizing beamforming technology and four antennas to focus signal strength precisely where you need it.

Product Description OF WIFI-6 AC1200 Full Router JIR-AC666R2:

Product Specification:

| |
|--|
| High Master Frequency: Processor operating main frequency up to 1.0 GHz, 1600 DMIPs, high specification, high power coverage |
| QOS Intelligent Bandwidth: It can reasonably allocate and download bandwidth resources according to the needs of different users |
| Multi-level security: support IP filtering, MAC filtering, SSID hiding, advanced encryption and other multi-level security precautions |
| 2T2R technology: signal dual channel transmission, dual channel reception |
| WIFI-6 AC1200 Full Router JIR-AC666R2 |

Specification parameters OF WIFI 6:

| | |
|------------------------|--|
| Chipset | RTL8197FH-VG4+RTL8812FR+RTL8367RB-VC |
| FLASH | 8MB |
| DDR2 | 64MB |
| Wireless rate | 2.4 GHz?300Mbps&2*2 |
| | 5GHz?867Mbps&2*2 |
| Antenna | 4*5 dBi External antenna |
| Interface | 1* GE WAN+3* GE LAN |
| Button | 1* RESET+1* WPS |
| Indicator | POWER WAN 2.4G 5G WPS |
| Wi-Fi Agreement | IEEE 802.11b/g/n/ac support |
| MIMO modalities | MU-MIMO |
| Work model | Routing mode, AP mode, and relay mode |
| Management approach | Chinese WEB Remote Management |
| State | System state, interface state, and routing table |
| Wireless Configuration | Wi-Fi Basic Parameter Configuration / Blacklist |
| Network settings | Working mode: LAN/WAN address setting |
| System | System properties/password modification/backup upgrade/restart |
| Setup Wizard | Quick Configuration Wizard |
| MTBF | >20000 H |
| power consumption | ?9 W |
| Working temperature | 0??40? |
| Storage temperature | -40??70? |
| Working humidity | 10%~95%, no condensation |
| Storage humidity | 5%~95%, no condensation |
| Power adapter | DC 12V/1A |

Hear some related drop-cable links below:

WIFI-6 AX1500M Router JIR-AX940R:

WIFI-6 AC1200 Router JIR-AC654R:

© 2026 | Phone: +977 9851248419 | Email: info@dtechtrading.com | Website: <https://demoshop.com>. All rights reserved.