

Fiber Optic Patch Cord Simplex FC UPC to LC UPC

Fiber Optic Patch Cord Simplex FC UPC to LC UPC

Variants

5M 3.00mm 7M 3.00mm 10M 3.00mm

Details

1. Product Description: Patch Cord FC UPC to LC UPC 3.00mm Simplex

Introduction: The **Patch Cord FC UPC to LC UPC 3.00mm Simplex** is a high-performance fiber optic cable designed for efficient and reliable data transmission in single-mode applications. This patch cord features **FC UPC (Ultra Physical Contact)** on one end and **LC UPC (Ultra Physical Contact)** connectors on the other. The **length** and **3.00mm outer jacket** provide a flexible, durable solution for medium-distance fiber optic connections in data centers, telecommunications, and high-speed networking applications. The **Simplex configuration** ensures one-way transmission, ideal for point-to-point fiber connections.

Technical Parameters:

Connector Type: FC UPC to LC UPC (Ultra Physical Contact)

Cable Type: Simplex

Cable Diameter: 3.00mm

Fiber Mode: Single-mode (SM)

Fiber Type: OS2 (Single-Mode Fiber)

Insertion Loss: 0.3 dB (typical)

Return Loss: >50 dB (typical for FC and LC UPC connectors)

Operating Temperature: -40°C to +75°C

Storage Temperature: -40°C to +85°C

Compliance: RoHS Compliant, UL Listed

Attenuation: 0.4 dB/km (at 1310nm)

Key Features:

FC UPC to LC UPC Connectors: The **FC UPC** and **LC UPC** connectors are engineered for high-precision, low-loss data transmission. The **UPC** finish minimizes signal reflection and insertion loss, ensuring optimal signal quality and reliable performance.

Simplex Configuration: The **Simplex design** supports one-way fiber transmission, which is perfect for connecting devices that require unidirectional communication, such as switches, routers, and optical networks.

3.00mm Durable Jacket: The **3.00mm outer jacket** offers robust protection against physical damage, wear, and environmental stress while maintaining flexibility for easy routing and installation.

Single-Mode OS2 Fiber: The **OS2 single-mode fiber** minimizes signal loss over long distances, making it ideal for high-bandwidth applications, ensuring clear and uninterrupted data transfer.

Low Insertion Loss & High Return Loss: This patch cord is designed to minimize **insertion loss** and provide **high return loss**, ensuring that your network remains clear and efficient over extended periods of time.

Product Advantages:

High-Quality Data Transmission: The **FC UPC to LC UPC connectors** ensure excellent performance, with low insertion loss and high return loss, making this patch cord ideal for fiber optic systems that require consistent and high-quality signal transmission.

Ideal for Medium-Distance Applications: With this patch cord is perfectly suited for installations requiring medium-range fiber connections, such as **data centers**, **telecommunications**, and **network infrastructure**.

Durability and Flexibility: The **3.00mm jacket** offers both durability and flexibility, providing robust protection against physical wear while maintaining ease of installation in tight spaces.

Perfect for Single-Mode Networks: The **OS2 single-mode fiber** ensures minimal signal degradation, making this patch cord suitable for long-distance applications with high bandwidth requirements.

Cost-Effective Solution: The **high-quality construction** ensures longevity and reliability, providing a cost-effective and durable solution for fiber optic network installations.

Compact and Efficient: The **Simplex configuration** makes this patch cord ideal for environments where only one-way communication is needed, ensuring efficient use of space and resources in networking setups.

The **Patch Cord FC UPC to LC UPC 3.00mm Simplex** is the ideal solution for medium-distance, high-performance fiber optic connections. Whether used in **data centers**, **telecommunications**, or other networking systems, this patch cord ensures reliable data transmission, minimal signal loss, and long-term durability, making it a cost-effective choice for fiber optic network infrastructure.