

Fiber Optic Patch Cord Simplex FC UPC to LC UPC

Fiber Optic Patch Cord Simplex FC UPC to LC UPC

Variants

7M 3.00mm 10M 3.00mm 5M 3.00mm

Details

Patch Cord FC UPC to LC UPC Simplex

The FC UPC to LC UPC 3.00mm Simplex Patch Cord is a high-performance fiber optic cable designed for reliable single-mode transmission. It features FC UPC and LC UPC connectors, ensuring low signal loss and stable performance for telecom, data centers, and high-speed networking applications.

Technical Specifications

Category	Specification
Connector Type	FC UPC to LC UPC
Polish Type	UPC to UPC
Cable Type	Simplex
Cable Diameter	3.00 mm
Fiber Mode	Single-mode (SM)
Fiber Type	OS2 (9/125 μ m)
Insertion Loss	< 0.3 dB (Typical)
Return Loss	> 50 dB

Attenuation	? 0.4 dB/km @ 1310 nm
Operating Temperature	-40°C to +75°C
Storage Temperature	-40°C to +85°C
Compliance	RoHS Compliant, UL Listed

Key Features

Features
FC UPC and LC UPC connectors ensure stable and low-loss transmission
Simplex design for one-way fiber communication
3.00mm outer jacket for enhanced protection and flexibility
OS2 fiber supports long-distance and high-speed transmission
Low insertion loss and high return loss for better network performance

Product Advantages

Advantages
High-quality signal transmission with minimal loss
Ideal for telecom, data center, and enterprise networks
Durable and flexible design for easy installation
Supports long-distance fiber communication
Cost-effective and long-lasting solution